

Fixing roof tiles in valleys

(May 2024) (Second issue – supersedes December 2024)

The Technical Guidance Notes are produced by NHBC as guidance solely for our builder customers as to how to interpret the technical requirements in relation to the warranty cover provided by NHBC under its Buildmark, Buildmark Choice, Buildmark Link, Buildmark Solo, Buildmark Connect or any similar product from time to time. It has not been created or intended for distribution or use outside of that purpose. The information contained in this Technical Guidance Note does not constitute advice and is not to be relied upon by any third party. Nothing in this Technical Guidance Note is intended to, nor should it be taken to, create any legal or contractual relationship. Any third party who chooses to rely upon the information contained in the Technical Guidance Notes shall do so entirely at their own risk and NHBC accepts no duty of care or liability, however caused, in connection with its use or reliance by any third party.

Question

Is it acceptable to fix roof tiles in open inclined roof valleys without mortar bedding?

Considerations

- NHBC Standards clause 7.2-S12(d) refers to bedding roof tiles in mortar when using valley tiles or lead-lined valleys.
- BS 5534 'code of practice for slating and tiling' says roof tiles should be mechanically fixed at each side of valleys.
- Roof tile manufacturers' literature refers to the bedding of their roof tiles to lined valley gutters and valley tiles.
- Manufacturers of GRP valley gutter liner systems generally provide edging strips on their liners for bedding of roof tiles.
- Bedding of tiles provides a method for securing small cut sections of tile that extend beyond the tiling battens and which cannot be mechanically fixed.
- In parts of Scotland it has been common practice not to bed roof tiles in valleys. Some roof tile manufacturers recognise this and advise on the use of extra wide tiles to avoid small cut tiles or the use of additional intermediate tiling battens to provide a means for mechanically fixing each section of tile.

Answer

Valley tiles should be cut and bedded in mortar to help secure the tile and prevent entry of wind driven rain, large insects and birds into the batten space.

In areas where it has been common practice (i.e. parts of Scotland), non-bedding of roof tiles in valleys can be accepted provided all cut tiles are mechanically fixed and a mesh or comb filler is used to prevent the entry of birds and large insects into the batten spaces. Where there is any query on the method of dry fixing being employed written confirmation should be provided by the roof tile manufacturer.



NHBC, NHBC House, Davy Avenue, Knowlhill, Milton Keynes, Bucks MK5 8FP
Tel: 0344 633 1000 Web: nhbc.co.uk

National House-Building Council (NHBC) is authorised by the Prudential Regulation Authority and regulated by the Financial Conduct Authority and the Prudential Regulation Authority for carrying on insurance business and insurance distribution activities.

NHBC is registered in England and Wales under company number 00320784. NHBC's registered address is NHBC House, Davy Avenue, Knowlhill, Milton Keynes, Buckinghamshire, MK5 8FP. Note that only certain parts of our products and services are within the scope of UK financial services regulations. For more information on our products and services, please see our website [nhbc.co.uk](https://www.nhbc.co.uk) or your NHBC product documentation.